



BBGA2.MH63503 - Battery Cells for Use in Stationary and/or Transport Applications - Component


Battery Cells for Use in Stationary and/or Transport Applications - Component

EVE POWER Co., Ltd.

No. 68, Jingnan Avenue, Jingmen Hi-tech Zone
Jingmen, 448000 China

MH63503

Model	Chemistry	Form Factor	Standard	Nom Voltage, V dc	Capacity, Ah	Use Temp Range, °C	Max Charging Rate		Max Discharging Rate
							Current, A	Voltage, V dc	
Battery cell									
LF105	LiFePO4	Prismatic	UL 2580	3.2	105	-20 to 55 for discharge, 0 to 55 for charge	105	3.65	315
LF50K	LiFePO4	Prismatic	UL 1973	3.2	50	-20 to 55 for discharge, 0 to 55 for charge	150	3.75	150
LF280K	LiFePO4	Prismatic	UL 1973	3.2	280	-20 to 55 for discharge, 0 to 55 for charge	280	3.65	280
LF32	LiFePO4	Prismatic	UL 1973	3.2	32	-20 to 55 for discharge, 0 to 55 for charge	32	3.65	32

Marking: Company name, model designation and the Recognized Component Mark 

Last Updated on 2021-05-24

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"